

BRACKET | BRKT-030

BRKT-030

LPDA 92 LTE HORIZONTAL MOUNTING BRACKET

Physical and Mechanical Properties of Aluminium

Die-casting Alloys

Density :	2.82 g/cm ³
Heat Capacity:	0.963 J/g.K
Thermal Conductivity:	92 W/m.K
Melting Range:	516-582°C
Tensile Strength, Ultimate:	331 MPa
Tensile Strength, Yield:	165 MPa
Elongation:	2.5%

Mechanical Specifications

Product Dimensions (L x W x D):	127x100x697mm
Packaged Dimensions:	140x106x106 mm
Weight:	0.337kg
Packaged Weight:	0.396kg
Material:	Cast Aluminium ADC12

Environmental Specifications

Wind Survival:	160km/h
Temperature Range (Operating):	- 40°C to +70°C
Conditions:	Outdoor
Operating Relative Humidity:	Up to 98%
Storage Humidity:	5% to 95% - non condensing
Storage Temperature:	-- 40° to + 70°

Product Box Contents

Product:	A-BRKT-030
----------	------------



Ordering Information

Commercial name:	BRKT-030
Order Product Code:	A-BRKT-030

Additional Accessories Available

For more detailed information and availability in your region, visit our web site: www.poynting.tech

Certification Approvals and Standards

Flammability rating:	UL:94-V1
Water Ingress Protection Ratio/Standard:	IP65(NEMA 4x)
IK Code:	IK08
Salt Spray:	MIL-STD 810F/ASTM B117
Product Safety:	Complies with UL, CE, EN, CSA and IEC standards



Contact Poynting

Poynting Antennas (Pty) Ltd - Head Office

Unit 4, N1 Industrial Park
Landmarks Avenue,
Samrand, 0157
South Africa

Phone: +27 (0) 12 657 0050

E-mail: sales@poynting.co.za

Poynting Europe

Regus Business Center Neue Messe Riem
Kronstadter Straße 4
81677 München
Germany

Phone: +49 89 208026538

E-mail: sales-europe@poynting.tech

BRKT-030

©2015 Poynting Antennas (Pty) Ltd. All rights reserved.
Product Specifications may change without prior notice
Revised: September 2015

Regulatory Compliance: RoHS 2011/65/EU Compliant | ISO 9001:2008
Document version: TS-A-BRKT-030
www.poynting.tech